

HD-SDI Cameras



CAMERA SBC-20HD-SDI 2.0MPIX

Resolution: 1280 x 720; HD-SDI 720p; Min. illumination: 0.1 Lux / F1.2; Lens: 2.8-10 mm; Sensor: 1/3" 2.0Mpix Panasonic CMOS; Frame rate: 30 fps; Video bitrate: 1.485 Gb/s; **Sense-UP, 3D-DNR, ICR filter**



CAMERA SBC-120HD-SDI 2.1MPIX

Resolution: 1920 x 1080; HD-SDI 1080p, 720p; Min. illumination: 0.1 Lux / F1.2; Lens: 2.8-10 mm; Sensor: 1/3" 2.1 Mpix CMOS; Frame rate: 30 fps; Video bitrate: 1.485 Gb/s; Vandal-proof; **3D-DNR, WDR, HLM, ICR filter**



CAMERA GEMINI-022D-13 HD-SDI 2.1MPIX

Resolution: 1920 x 1080; HD-SDI 1080p; Range of IR illumination: 15m; Lens: 2.8-12 mm; Sensor: 1/3" 2.1 Mpix CMOS; **Sense-UP, 3D-DNR, HSBLC, Sharpness, ICR filter**



CAMERA GEMINI-022D-16 HD-SDI 2.1MPIX

Resolution: 1920 x 1080; HD-SDI 1080p; Range of IR illumination: 15m; Lens: 2.8-12 mm; Sensor: 1/3" 2.1 Mpix CMOS; Vandal-proof; **Sense-UP, 3D-DNR, HSBLC, D-zoom, PIP, ICR filter**



CAMERA GEMINI-020B HD-SDI 2.1MPIX

Resolution: 1920 x 1080; HD-SDI 1080p; Min. illumination: color 0.15Lux, B/W 0.01Lux, with Sense-UP 0.0008Lux; Sensor: 1/3" 2.1 Mpix CMOS; **Sense-UP, 3D-DNR, HSBLC, D-zoom, PIP, RS-485, ICR filter**



CAMERA SBC-220HD-SDI 2.1MPIX

Resolution: 1920 x 1080; HD-SDI 1080p, 720p; Min. illumination: 0.1 Lux / F1.2; Sensor: 1/3" 2.1 Mpix; Frame rate: 30 fps; Video bitrate: 1.485 Gb/s; **3D-DNR, WDR, HLM, ICR filter**



CAMERA SBC-520HD-SDI 2.1MPIX

Resolution: 1920 x 1080; HD-SDI 1080p, 720p; Range of IR illumination: 30m; Lens: 2.8-10 mm; Sensor: 1/3" 2.1 Mpix CMOS; Frame rate: 30 fps; Video bitrate: 1.485 Gb/s; Vandal-proof; **3D-DNR, WDR, HLM, ICR filter**



CAMERA GEMINI-022-43 HD-SDI 2.1MPIX

Resolution: 1920 x 1080; HD-SDI 1080p, 720p; Range of IR illumination: 50m; Lens: 2.8-12 mm; Sensor: 1/3" Panasonic 2.1 Mpix CMOS; Vandal-proof, hermetic; **Sense-UP, 3D-DNR, HSBLC, D-zoom, PIP, ICR filter**



CAMERA [SBC-2020HD-SDI](#) ICR 2.1MPIX 1.7-94mm SPEED DOME OUTDOOR

Resolution: 1920 x 1080; HD-SDI 1080i; Min. illumination: color 0.5Lux, B/W: 0.095Lux (with Sense-UP); Lens: 1.7 - 94 mm
Sensor: 1/3" 2.1 Mpix CMOS; Metal housing, Hermetic, IP66; **Sense-UP, WDR, Noise Reduction, ICR filter**

HD-SDI Digital Video Recorders



DVR [RC-4600HD-SDI](#) 4 CHANNELS +LAN +REMOTE +USB +VGA +HDMI +e-SATA

Frame rate: 60fps @ 1280x720, **28fps @ 1920x1080**; Compression: H.264
HDDs: Max. 2 x 2TB (SATA) + 1 x 2TB (E-SATA);
Multi-operation: Triplex; 4 x Audio;
Very good network software; HD-SDI interface;



DVR [RC-4700HD-SDI](#) 4 CHANNELS +LAN +REMOTE +USB +VGA +HDMI +e-SATA

Frame rate: **120fps @ 1280x720 (HD-SDI 720p) and 640x360**; Compression: H.264
HDDs: Max. 4 x 2TB (SATA); Multi-operation: PentaPlex; 4 x Audio;
Very good network software.



DVR [RC-4700FHD-SDI](#) 4 CHANNELS +LAN +REMOTE +USB +VGA +HDMI +e-SATA

Frame rate: 120fps @ 640x360, 120fps @ 1280x720, 120fps @ 1920x540, **60fps @ 1920x1080**; Compression: H.264;
HDDs: Max. 4 x 3TB (SATA) + 2 x 3TB (E-SATA);
Multi-operation: Triplex
4 x Audio;
Very good network software; HD-SDI interface;



DVR [RC-8600HD-SDI](#) 8 CHANNELS +LAN +REMOTE +USB +VGA +HDMI +e-SATA

Frame rate: 120fps @ 640x360, 96fps @ 1280x720, 80fps @ 1920x540, **40fps @ 1920x1080**; Compression: H.264
HDDs: Max. 2 x 2TB (SATA) + 1 x 2TB (E-SATA);
Multi-operation: Triplex; 8 x Audio;
Very good network software; HD-SDI interface;



DVR [RC-16600HD-SDI](#) 16 CHANNELS +LAN +REMOTE +USB +VGA +HDMI +e-SATA

Frame rate: 240fps @ 640x360, 192fps @ 1280x720, 160fps @ 1920x540, **80fps @ 1920x1080**;
Compression: H.264
HDDs: Max. 4 x 2TB (SATA) + 1 x 2TB (E-SATA); Multi-operation: Triplex; 16 x Audio
Very good network software; HD-SDI interface;